

100Mbps Fiber-NMS Ethernet Converter

10/100Mbps TP to 100Mbps SFP Management Fast Ethernet Converter



SFC200-SCM

- Reliable Optical Communication using Management Function
- Converts UTP to Fiber Optic for Long distance Transmission
- RJ-45 Port Auto MDI/MDI-X
- 10/100Mbps Throughput, Auto Negotiation
- 10/100Mbps, Full/Half-duplex Manual mode
- Supports Built-in Power Type
- LED Indication for Network Connection Status
- IP based Management Function
- Auto Scan Management Program
- Alarm Function during Equipment Malfunction or Cable Disconnection
- Optical Port Monitoring: Temperature, Voltage, Current, Optical Tx/Rx values

Specifications

Technology	- Standard	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX/100Base-FX
Interface	- RJ45 Ports	1-Port 10/100Mbps TP, Auto-Negotiation, Auto MDI/MDI-X TP/STP Cat. 3, 4, 5, 6 Cable EIA/TIA-568 100-ohm(100m)
	- Fiber Ports	1-Port 100Mbps SC connector Multi-mode : 62.5/125 μ m (2km)
	- LED Indicators	Per unit : Power Per port(TX) : Link, Activity, FDX/HDX, speed Per port(FX) : Link, Activity
Performance	- Data transfer	100Mbps
Environmental	- Temperature	Operation: 0°C ~ 60°C, Store: -20°C ~80°C
	- Humidity	5 ~ 95% (Non-condensing)
	- Installation	Stand alone, Center Mount Module Type
Input Voltage		DC 5V 2A SMPS Adapter
Dimensions		71mm(W) x 94mm(D) x 26mm(H)

Ordering Information

Model Name	Description
SFC200-SCM	10/100Mbps-TX to 100Mbps-FX Fast Ethernet Converter, Multi-mode 2km, 1310nm, SC Type