

SFC4000C

이더넷 광 스위치

1Gbps TP 8포트(COMBO)

+ 1G SFP 24 슬롯

+ 10G SFP 4슬롯 Managed Switch



제품 특징

- TP 8포트(콤보) + SFP 1G 24슬롯 + SFP 10G 4슬롯 매니지먼트 스위치
- 4k VLAN entries , GVRP, 802.1D(STP) , 802.1W(RSTP) , 802.1S(MSTP)
- IGMP v1/v2/v3, IGMP Snooping , Static routing
- MLD v1/v2 , MLD Snooping
- Port isolation, port security , DHCP Snooping
- IEEE802.1x certification, Radius , TACACS+
- Static and LACP link aggregation , EAPS , ERPS
- Console, Telnet, SSH, HTTP, HTTPS, SNMPv1/v2/v3, RMON, NTP, SPAN, RSPAN

제품 사양

표준	
Standard	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) 100Base-T: UTP category 5, 5e cable (maximum 100m) 1000Base-T: UTP category 5e, 6 cable (maximum 100m) 1000Base-X: MMF, SMF 10GBase-X: MMF, SMF
인터페이스	
RJ45 포트	1Gbps TP 8포트(Combo)
광포트	1Gbps SFP 24슬롯 + 10Gbps SFP 4슬롯
LED 표시	Power, System, Port link/activity
성능	
Back Plane	Switch Fabric 128Gbps, Forwarding rate 95.2Mpps
Flash	32MB
DRAM	256MB
MAC	16K
동작환경	
온도범위	동작온도: 0 ~ 50 °C, 보관온도: -20 ~ 70 °C
습도	10 ~ 90%(이슬이 맺히지 않을 것)
입력전원	
-	AC 100 ~ 240V
크기	
WxDxH	440x280x44(mm)

SFP 정보

모델명	사양
SFP+10G-LR/SFP+10G-SR	10G, Single-mode, 10km, 1310nm, LC/ 10G, Multi-mode, 300m, 850nm, LC
SFP-LX20/SFP-SX	1G, Single-mode, 20km, 1310nm, LC/ 1G, Multi-mode, 220m, 850nm, LC
SFP-SM20/SFP-MM	100M, Single-mode, 20km, 1310nm, LC/ 10G, Multi-mode, 2km, 1310nm, LC
SFP-SMW/SFP-LXW	100M, Single-mode, 20km, 1-Fiber(WDM)/ 1G, Single-mode, 20km, 1-Fiber(WDM)