

SFC410BT-BP_2x2

10/100/1000Mbps TP 8포트 PoE + 100M/1G/10Gbps SFP 4슬롯 + BYPASS 2x2



- 10M/100M/1000Mbps TP 8포트 PoE + 100M/1G/10Gbps SFP+ 4슬롯
- Fiber BYPASS LC type 2x2
- 웹 관리, 콘솔, Telnet, SSH, SNMP, RMON, Syslog
- Scan Manager Program 지원
- STP (IEEE802.1D) / RSTP (IEEE802.1w) / MSTP (IEEE802.1s)
- Port VLAN & VLAN Tagging(IEEE802.1Q)
- S-Ring(절체, 복구 30ms), Dual-Ring
- ERPS Ring Protocol (G.8032 ERPS)
- IP Multicast support (IGMP/MLD)
- Priority Queue Support (8 Queue per port)

제품사양

표준	- Standard	IEEE 802.3/3u/3ab/3z/ae 10Base-T / 100Base-Tx/Fx / 1000Base-T / Gigabit & 10G Fiber IEEE 802.1D/w/s Spanning Tree / Rapid Spanning Tree / Multiple Spanning Tree Protocol IEEE 802.1Q VLAN Tagging, IEEE 802.3ad LACP, IEEE 802.3af/at/bt Power over Ethernet ITU-T G.8032 Ethernet Ring Protection Switching
인터페이스	- RJ45 포트	10/100/1000Mbps TP 8포트, Auto MDI/MDI-X TP/STP Cat. 3, 4, 5, 6 Cable EIA/TIA-568 100-ohm(100m) 4 PoE af/at + 4 PoE af/at/bt, PoE Power Budget : Max. 240W
	- 광 포트	100/1000Mbps SFP or 10G SFP+ 4 슬롯 Multi mode : 50/125 μ m, 62.5/125 μ m, Single mode : 9/125 μ m
	- Digital I/O	1 Input, 1 Output
	- BYPASS	LC Type 2x2
성능	- Back Plane	MAC Table : 32K, Switch Fabric : 96Gbps, Throughput 71.4Mpps, Jumbo Frame : 10K,
LED Indicator	- Device	Per Unit : Power, Fault/Alarm, Ring Master
	- Port	TP Port : Link/Act(Green), PoE On(Orange) Fiber Slot : 100/1000Mbps Link/Act(Orange), 10Gbps Link/Act(Green)
동작환경	- 온도범위	동작온도: -40°C ~ 80°C, 보관온도: -45°C ~ 85°C
	- 습도	5 ~ 95% (이슬이 맺히지 않을 것)
전원	- 입력전원	100~240VAC, 50/60Hz
	- 소비전력	무부하 소비전력 : 18.9W / 풀부하 소비전력 : 290.4W (PoE Max. 240W)
크기		310mm(W) x 248.8mm(D) x 44mm(H)

주문정보

모델명	사양
SFC410BT-BP_2x2	10/100/1000Mbps 4PoE(at) + 10/100/1000Mbps 4PoE(bt) + 100M/1G/10Gbps SFP 4슬롯, BYPASS - LC type 2x2
SFP-SX	SFP(1.25Gbps) 광모듈, LC 커넥터, 멀티모드, 전송거리 220/550m, 850nm
SFP-LX	SFP(1.25Gbps) 광모듈, LC 커넥터, 싱글모드, 전송거리 20km, 1310nm
SFP-LXH	SFP(1.25Gbps) 광모듈, LC 커넥터, 싱글모드, 전송거리 10km, 1310nm, -40°C ~ 80°C
SFP-10G-SR	SFP+(10.31Gbps) 광모듈, LC 커넥터, 멀티모드, 전송거리 300m, 850nm
SFP+10G-LR	SFP+(10.31Gbps) 광모듈, LC 커넥터, 싱글모드, 전송거리 10km, 1310nm