

2.5G 산업용 이더넷

10/100/1000-T 8-Port + 100/1000/2.5Gbps SFP 2-Slots + 100/1000Mbps SFP 2-Slots



- 10/100/1000-T 8포트 + SFP 4슬롯
- SFP 2슬롯(100/1000/2.5Gbps), SFP 2슬롯(100/1000Mbps)
- ARP Inspection, DHCP Snooping, IP Source Guard support
- STP(IEEE 802.1D) /RSTP(IEEE 802.1w) /MSTP(IEEE 802.1Q)
- Carrier Ethernet (ERPS)
- S-Ring, Dual Ring 지원
- IPv4/IPv6 지원
- IPMC support (IGMP/MLD)
- Auto Scan Manager Program (Scan, IP Setting)

제품사양

표준	Standard	IEEE 802.3/3u/3ab/3z 10Base-T / 100Base-TX and 100Base-FX / 1000Base-T /Gigabit Fiber IEEE 802.1w Rapid spanning tree protocol IEEE 802.1Q VLAN Tagging IEEE 802.3ad LACP
인터페이스	RJ45 포트	8-Ports 10/100/1000Base-T(X), Auto MDI/MDI-X UTP/STP Cat. 3, 4, 5, 6 Cable EIA/TIA-568 100-ohm(100m)
	광포트	100/1000Base SFP Slot, 100/1000/2.5Gbps SFP Slot Multi mode: 50/125 μ m, 62.5/125 μ m, Single mode: 9/125 μ m
	LED 표시	Per unit: Power, Power Input 1, Power Input2, Fault/Alarm, Ring Master 1000Base-T Port: Speed(1000Mbps Yellow), Link/Activity (Green) Mini-GBIC: Link/Activity (Green)
	I/O Device	2 Input, 2 Output
성능	Back Plane	Switching Fabric 30Gbps
	Mac Address	8K MAC Address table
	설치방법	Wall Mount
동작환경	온도범위	동작온도 : -40 $^{\circ}$ C ~ 80 $^{\circ}$ C, 보관온도: -40 $^{\circ}$ C ~ 85 $^{\circ}$ C
	습도	5% ~ 95% (이슬이 맺히지 않을것)
입력전원		DC 12V~56V, 전원이중화, 극성보호회로
크기		153.8mm(W) x 151.2mm(D) x 44.4mm(H)

주문정보

모델명	사양
SFC8000G	10/100/1000Mbps 10/100/1000-T 8포트 + 100/1000/2.5Gbps SFP 2슬롯+ 100/1000Mbps SFP 2슬롯
SFP-SX	SFP(1.25Gb) 광모듈, 멀티모드, 전송거리 220/550m, 850nm, LC 커넥터
SFP-LX20	SFP(1.25Gb) 광모듈, 싱글모드, 전송거리 20Km, 1310nm, LC 커넥터