

Managed Industrial 2.5Gigabit Ethernet Switch

4-Ports 10/100/1000Mbps TP + 2-Slots 100/1000/2.5Gbps SFP



SFC8000S

- Gigabit S-Ring(Recovery Time < 50ms)
- Compact, Space Saving Package
- 2-SFP Slots 100/1000/2.5Gbps
- I/O interface 2 Input, 2 Output
- Carrier Ethernet(ERPS)
- STP(IEEE 802.1D), RSTP(IEEE 802.1w), MSTP(IEEE 802.1Q)
- Full IEEE 802.3 Compliant
- Auto Sensing Speed and Flow Control
- Full Wire Speed Communications
- IPMC support(IGMP/MLD), DHCP Client
- Web Based management, Telnet, SNMP, Syslog
- Auto Scan Manager Program(Scan, IP Setting)

제품사양

표준	- Standard	IEEE 802.3/3u/3ab/3z 10Base-T / 100Base-TX and 100Base-FX / 1000Base-T / Gigabit Fiber IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1Q VLAN Tagging IEEE 802.3ad LACP
인터페이스	- RJ45 포트	4-Ports 10/100/1000Mbps TP, Auto MDI/MDI-X TP/STP Cat. 3, 4, 5, 6 Cable EIA/TIA-568 100-ohm(100m)
	- 광포트	100/1000/2.5Gbps SFP Slot Multi mode: 50/125 μ m, 62.5/125 μ m, Single mode: 9/125 μ m
	- LED 표시	Per unit: Power, Power Input1, Power Input2, Fault/Alarm, Ring Master 1000Mbps TP Port: Speed(1000Mbps Yellow), Link/Activity(Green), Mini-GBIC: Link/Activity(Green)
	- Input/Output	2 Input, 2 Output
성능	Back Plane	Switching Fabric 26Gbps
동작환경	- 온도범위	동작온도: -40°C ~ 80°C, 보관온도: -45°C ~ 85°C
	- 습도	5 ~ 95% (이슬이 맺히지 않을 것)
	- 설치방법	DIN-Rail, Panel mounting
입력전원		DC 12V~54V, Redundant DC Power input, Power polarity reverse protect
크기		41.3mm(W) x 106.3mm(D) x 112.3mm(H), IP30

주문정보

모델명	사양
SFC8000S	4-Ports 10/100/1000Mbps TP + 2-Slots 100/1000/2.5Gbps SFP, Compact Size
SFP-SX	SFP(1.25Gbps) Module, Multi-mode, 220/550m, 850nm, LC Type
SFP-LX	SFP(1.25Gbps) Module, Single-mode, 20Km, 1310nm, LC Type
SFP-LXH	SFP(1.25Gbps) Module, Industrial Single-mode, 10Km, 1310nm, LC Type